

```
[2006-HP-A5500-170]di cu
#
version 5.20.99, Release 5206
#
sysname 2006-HP-A5500-170
#
clock timezone Asia/Jrusalem minus 15:37:40
#
super password level 3 cipher $c$3$a1yLjk6QXFGV93O53A/TMvKR/omee0cWNw=
#
dhcp relay server-group 1 ip 10.10.12.2
#
irf mac-address persistent timer
irf auto-update enable
undo irf link-delay
#
domain default enable trustsec.net
#
ipv6
#
dot1x
dot1x retry 3
dot1x authentication-method eap
#
portal server iseportal ip 10.10.13.188 port 8443 url
https://10.10.13.188:8443/portal/gateway?portal=a6b8fa70-fc3e-11e4-a67c-005056bf2f0a&action=cwa

portal free-rule 10 source ip any destination ip any
#
mac-authentication
mac-authentication domain trustsec.net
mac-authentication user-name-format mac-address with-hyphen
#
password-recovery enable
#
radius-server client-ip 10.10.13.150 key cipher $c$3$kgga2MzbRRaA0zBTHn+WAGObOPOGnBM=
radius-server client-ip 10.10.13.188
#
acl number 3000
rule 0 permit ip destination 10.10.13.0 0.0.0.255
rule 5 permit tcp destination 10.10.13.0 0.0.0.255
rule 10 deny ip
rule 15 permit ip
acl number 3001
```

```
rule 0 permit ip
#
vlan 1
#
vlan 100
#
vlan 112
#
vlan 114
#
vlan 170
#
radius scheme radius1
server-type extended
primary authentication 10.10.13.186 key cipher $c$3$aXKjUgtRamdZSsYJKhqhts5MD65mtl=
primary accounting 10.10.13.186 key cipher $c$3$oyhWEiXe2ldknsQr5wi+2xxj+d7xqHw=
key authentication cipher $c$3$GTyquXC6qbalxf5PdC+ZySyCymHTKU=
key accounting cipher $c$3$aV8sN5uewCVwk/g+gobB4bfW9bov1Sg=
user-name-format without-domain
#
domain system
access-limit disable
state active
idle-cut disable
self-service-url disable
domain trustsec.net
authentication default radius-scheme radius1
authorization default radius-scheme radius1
accounting default radius-scheme radius1
authentication lan-access radius-scheme radius1
authorization lan-access radius-scheme radius1
accounting lan-access radius-scheme radius1
authentication portal radius-scheme radius1
authorization portal radius-scheme radius1
accounting portal radius-scheme radius1
access-limit disable
state active
idle-cut disable
self-service-url disable
#
user-group system
group-attribute allow-guest
#
local-user admin
```

```
password cipher $c$3$7XpT1n5GwMeL1PkC0nKpZVXrpmQ2woo2/Ra6ZA==  
authorization-attribute idle-cut 20  
service-type lan-access  
#  
cwmp  
undo cwmp enable  
#  
interface NULL0  
#  
interface Vlan-interface112  
ip address 10.10.112.239 255.255.255.0  
dhcp select relay  
dhcp relay server-select 1  
dhcp relay information enable  
portal server iseportal method direct  
#  
interface Vlan-interface170  
ip address 10.10.170.249 255.255.255.0  
dhcp select relay  
dhcp relay server-select 1  
dhcp relay information enable  
#  
interface GigabitEthernet1/0/1  
port link-mode bridge  
port link-type hybrid  
undo port hybrid vlan 1  
port hybrid vlan 112 untagged  
port hybrid pvid vlan 112  
mac-vlan enable  
mac-authentication  
mac-authentication domain trustsec.net  
undo dot1x handshake  
dot1x  
dhcp-snooping information enable  
dhcp-snooping information format verbose node-identifier sysname  
#  
interface GigabitEthernet1/0/2  
port link-mode bridge  
#  
interface GigabitEthernet1/0/3  
port link-mode bridge  
#  
interface GigabitEthernet1/0/4  
port link-mode bridge
```

```
#  
interface GigabitEthernet1/0/5  
port link-mode bridge  
#  
interface GigabitEthernet1/0/6  
port link-mode bridge  
#  
interface GigabitEthernet1/0/7  
port link-mode bridge  
#  
interface GigabitEthernet1/0/8  
port link-mode bridge  
#  
interface GigabitEthernet1/0/9  
port link-mode bridge  
#  
interface GigabitEthernet1/0/10  
port link-mode bridge  
#  
interface GigabitEthernet1/0/11  
port link-mode bridge  
#  
interface GigabitEthernet1/0/12  
port link-mode bridge  
#  
interface GigabitEthernet1/0/13  
port link-mode bridge  
#  
interface GigabitEthernet1/0/14  
port link-mode bridge  
#  
interface GigabitEthernet1/0/15  
port link-mode bridge  
#  
interface GigabitEthernet1/0/16  
port link-mode bridge  
#  
interface GigabitEthernet1/0/17  
port link-mode bridge  
#  
interface GigabitEthernet1/0/18  
port link-mode bridge  
#  
interface GigabitEthernet1/0/19
```

```
port link-mode bridge
#
interface GigabitEthernet1/0/20
port link-mode bridge
#
interface GigabitEthernet1/0/21
port link-mode bridge
#
interface GigabitEthernet1/0/22
port link-mode bridge
#
interface GigabitEthernet1/0/23
port link-mode bridge
#
interface GigabitEthernet1/0/24
port link-mode bridge
port link-type trunk
port trunk permit vlan all
dhcp-snooping trust
#
interface GigabitEthernet1/0/25
port link-mode bridge
#
interface GigabitEthernet1/0/26
port link-mode bridge
#
interface GigabitEthernet1/0/27
port link-mode bridge
#
interface GigabitEthernet1/0/28
port link-mode bridge
#
interface M-GigabitEthernet0/0/0
#
interface Ten-GigabitEthernet1/0/29
port link-mode bridge
#
interface Ten-GigabitEthernet1/0/30
port link-mode bridge
#
dhcp-snooping
#
ip route-static 0.0.0.0 0.0.0.0 10.10.170.253
#
```

```
info-center source DHCP channel 0
info-center logbuffer channel 0
info-center synchronous
info-center monitor channel 0
#
snmp-agent
snmp-agent local-engineid 800063A2037848590D0A45
snmp-agent community read 123456
snmp-agent community write readme
snmp-agent community write writeme
snmp-agent log all
snmp-agent sys-info version all
#
dhcp enable
#
ip https enable
#
load xml-configuration
#
load tr069-configuration
#
user-interface aux 0
user-interface vty 0 15
#
return
[2006-HP-A5500-170]
```