

3rd-hp-2920# sh run

Running configuration:

; J9726A Configuration Editor; Created on release #WB.15.18.0007

; Ver #0a:20.14.29.eb.8f.fc.f3.ff.37.2d:99

hostname "3rd-hp-2920"

module 1 type j9726a

dhcp-snooping

dhcp-snooping authorized-server 10.10.12.2

dhcp-snooping authorized-server 10.10.13.186

dhcp-snooping authorized-server 10.10.13.188

dhcp-snooping authorized-server 10.10.13.245

dhcp-snooping authorized-server 10.10.13.246

dhcp-snooping authorized-server 10.10.13.249

dhcp-snooping vlan 54-55 112

radius-server host 10.10.13.249 key "acsi"

radius-server host 10.10.13.249 dyn-authorization

radius-server host 10.10.13.249 time-window 0

radius-server key "acsi"

timesync sntp

sntp unicast

sntp server priority 1 10.56.60.29

time timezone 180

ip access-list extended "PRE-AUTH"

exit

ip access-list extended "fullaccess"

```
10 permit ip 0.0.0.0 255.255.255.255 0.0.0.0 255.255.255.255
```

```
exit
```

```
ip default-gateway 10.10.48.253
```

```
ip dns server-address priority 1 10.10.12.11
```

```
interface 1
```

```
ip access-group "PRE-AUTH" in
```

```
dhcp-snooping trust
```

```
flow-control
```

```
exit
```

```
interface 2
```

```
dhcp-snooping trust
```

```
flow-control
```

```
exit
```

```
interface 3
```

```
flow-control
```

```
exit
```

```
interface 4
```

```
flow-control
```

```
exit
```

```
interface 5
```

```
flow-control
```

```
exit
```

```
interface 6
```

```
flow-control
```

```
exit
```

```
interface 7
```

```
flow-control
```

```
exit
```

```
interface 8
```

```
flow-control
exit
interface 9
    flow-control
    exit
interface 11
    flow-control
    exit
interface 24
    dhcp-snooping trust
    flow-control
    exit
snmp-server community "public" unrestricted
snmp-server community "writeme" operator unrestricted
snmp-server host 10.10.13.33 community "writeme"
aaa accounting update periodic 1
aaa accounting network start-stop radius
aaa accounting session-id common
aaa authentication port-access eap-radius
aaa port-access authenticator 1-2
aaa port-access authenticator 2 quiet-period 30
aaa port-access authenticator 2 logoff-period 862400
aaa port-access authenticator 2 client-limit 3
aaa port-access authenticator active
aaa port-access mac-based 2
aaa port-access mac-based 2 addr-limit 32
oobm
    ip address dhcp-bootp
    exit
```

vlan 1

name "DEFAULT_VLAN"

no untagged 2-24

untagged 1,A1-A2,B1-B2

no ip address

exit

vlan 5

name "VLAN5"

tagged 24

no ip address

exit

vlan 48

name "VLAN48"

untagged 2-24

ip address 10.10.48.249 255.255.255.0

exit

vlan 103

name "VLAN103"

tagged 24

no ip address

exit

vlan 104

name "VLAN104"

tagged 24

no ip address

exit

vlan 105

name "VLAN105"

tagged 24

no ip address

exit

vlan 112

name "VLAN112"

tagged 24

no ip address

exit

vlan 114

name "VLAN114"

tagged 24

no ip address

exit

vlan 115

name "VLAN115"

tagged 24

no ip address

exit

3rd-hp-2920#